Wolf PhoneStrip Tape

26.11.2024

Technical data

Wolf PhoneStrip Tape

-Adhesive tape for PhoneStrip with very high adhesive strength -Rigid PVC film, coated on one side with an adhesive-stable, cross-linked natural rubber adhesive

Intended use:

For sealing the cut edges when splitting the PhoneStrip decoupling strips.

Technical data:	
Carrier	Rigid PVC film
Beam thickness	0,033 mm
Total thickness	0,052 mm
Adhesive base	Natural rubber adhesive
Adhesive strength	≥ 1,4 N/cm ≥ 3,5 N/25 mm
Reißkraft	≥ 36 N/cm ≥ 90 N/25 mm
Elongation at break	30% to 80%
Temperature resistance	-30 °C to +70 °C
UV resistance	limited
Weather resistance	limited
Processing temperature	recommended > +5 °C
Storage stability at 18 °C and 55% RH	12 months

Storage: Store in a dry place at +5 °C to +25 °C and protected from UV light.

WOLF BAVARIA GmbH · Gutenbergstraße 8 · 91560 Heilsbronn · Tel.: +49 (0) 9872 95398-0 · Fax: +49 (0) 9872 95398-11 · www.wolf-bavaria.com We guarantee the consistent quality of our products, but reserve the right to make technical changes and further developments. The information on this data sheet is based on practical and scientific experience and corresponds to the manufacturer's specifications. As we have no influence on the variety of materials or their processing, we cannot assume any guarantee of properties in the sense of the latest BGH case law. This information is of a non-binding nature and does not exempt you from carrying out sufficient tests yourself.





Wolf PhoneStrip Tape