Wolf separating lane

26.11.2024



Technical data

Wolf separating lane

- is an insulating material covering paper according to DIN 18560 part 2, paragraph 6.1.2
- lies absolutely flat on the substrate
- prevents wrinkling
- is tear-resistant
- is coated with PE on both sides and can therefore be welded with hot air soaking is not possible.



Available as: [roll]	
Width	130 mm
Length	Roll of 100 metres
Thickness	Approx. 0,1 mm
Weight	130 g/m ²

Processing:

The Wolf separating membrane is rolled out onto the PowerFloor surface. Joints must be laid with an overlap of 5 cm to 10 cm. When doing so, lay the Wolf separating membrane right up to the edge insulation strip.

WOLF BAVARIA GmbH · Gutenbergstraße 8 · 91560 Heilsbronn · Tel.: +49 (0) 9872 95398-0 · Fax: +49 (0) 9872 95398-11 · www.wolf-bavaria.com We guarantee the consistent quality of our products, but reserve the right to make technical changes and further developments. The information on this data sheet is based on practical and scientific experience and corresponds to the manufacturer's specifications. As we have no influence on the variety of materials or their processing, we cannot assume any guarantee of properties in the sense of the latest BGH case law. This information is of a non-binding nature and does not exempt you from carrying out sufficient tests yourself.